



Safety Data Sheet

Issue Date: 27-Dec-2011

Revision Date: 28-May-2013

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Buckeye Ripsaw

Other means of identification

SDS # BE-002

Product Code 5025
UN/ID No UN1760

Recommended use of the chemical and restrictions on use

Recommended Use Floor finish stripper, water based.

Details of the supplier of the safety data sheet

Supplier Address

Buckeye International, Inc.
2700 Wagner Place
Maryland Heights, MO 63043 USA

Emergency Telephone Number

Company Phone Number 314-291-1900
24 Hr Medical Emergency Phone: 1-800-303-0441
651-632-8956
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Water clear liquid **Physical State** Liquid **Odor** Mild No fragrance added

Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

Signal Word

Danger

Hazard Statements

Causes severe skin burns and eye damage

**Precautionary Statements - Prevention**

Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a poison center or doctor/physician
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Immediately call a poison center or doctor/physician
 IF SWALLOWED: rinse mouth. Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Water	7732-18-5	>56.9
Benzyl alcohol	100-51-6	<15.0
Ethylene glycol monophenyl ether	122-99-6	<10.0
Ethanolamine	141-43-5	5
Octanoic Acid	124-07-2	<5.0
Sodium xylenesulfonate	1300-72-7	<4.0
Sodium metasilicate	6834-92-0	2
Sodium hydroxide	1310-73-2	1.1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures**Eye Contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing. Wash contaminated clothing before reuse. Get medical attention if irritation develops or persists.

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately.
Ingestion	Drink 1 or 2 glasses of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms	May cause redness, pain, and severe skin burns. Nausea. Headache. May cause skin irritation and defatting of skin with repeated/prolonged contact. Eye contact may cause redness or burning sensation.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Dermatitis or other pre-existing skin conditions may be aggravated by overexposure to this product.
---------------------------	--

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Toxic products of combustion.

Hazardous Combustion Products Oxides of sulfur. Carbon oxides. Nitrogen oxides (NOx). Silicon oxides.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions	Use personal protective equipment as required.
Environmental Precautions	See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Pick up with mop, wet/dry vac, or absorbent material. Rinse area with clear water and allow floor to dry before allowing traffic.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling	Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands, and any exposed skin thoroughly after handling. Use personal protection recommended in Section 8. Keep out of the reach of children.
--------------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Store at room temperature. Store away from incompatible materials. Store on low shelves.

Incompatible Materials Chlorine bleach. Acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethanolamine 141-43-5	STEL: 6 ppm TWA: 3 ppm	TWA: 3 ppm TWA: 6 mg/m ³ (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m ³ (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m ³	IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m ³ STEL: 6 ppm STEL: 15 mg/m ³
Sodium metasilicate 6834-92-0	2 mg/m ³	2 mg/m ³	-
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³ (vacated) Ceiling: 2 mg/m ³	IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Risk of contact: Wear approved safety goggles.

Skin and Body Protection Rubber gloves or other impervious gloves. Normal work clothing (long sleeved shirts and long pants) is recommended. Wear water or chemical resistant footwear when scrubbing floors.

Respiratory Protection No protection is ordinarily required under normal conditions of use and with adequate ventilation.

General Hygiene Considerations Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Mild No fragrance added
Appearance	Water clear liquid	Odor Threshold	Not determined
Color	Water clear		
Property	Values	Remarks • Method	
pH	12.6±0.3	1:4 dilution with DI water	12.3±0.2
Melting Point/Freezing Point	Not determined		
Boiling Point/Boiling Range	100 °C / 212 °F		
Flash Point	None		
Evaporation Rate	1.0	(Water = 1)	
Flammability (Solid, Gas)	n/a-liquid		
Upper Flammability Limits	Not applicable		
Lower Flammability Limit	Not applicable		
Vapor Pressure	Not determined		
Vapor Density	Not determined		
Specific Gravity	1.06		
Water Solubility	Infinite		

Solubility in other solvents	Not determined
Partition Coefficient	Not determined
Auto-ignition Temperature	Not determined
Decomposition Temperature	Not determined
Kinematic Viscosity	Not determined
Dynamic Viscosity	Not determined
Explosive Properties	Not determined
Oxidizing Properties	Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Contact with incompatible materials.

Incompatible Materials

Chlorine bleach. Acids.

Hazardous Decomposition Products

None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes severe eye damage.

Skin Contact Causes severe skin burns.

Inhalation Avoid breathing vapors or mists.

Ingestion May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Benzyl alcohol 100-51-6	= 1230 mg/kg (Rat)	= 2000 mg/kg (Rabbit)	= 8.8 mg/L (Rat) 4 h
Ethylene glycol monophenyl ether 122-99-6	= 1260 mg/kg (Rat)	= 5 mL/kg (Rabbit) = 14422 mg/kg (Rat)	-
Ethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1 mL/kg (Rabbit) = 1025 mg/kg (Rabbit)	-
Octanoic Acid 124-07-2	= 10080 mg/kg (Rat)	> 5 g/kg (Rabbit)	-
Sodium xylenesulfonate 1300-72-7	= 7200 mg/kg (Rat)	-	-
Sodium metasilicate 6834-92-0	= 600 mg/kg (Rat)	-	-

Sodium hydroxide 1310-73-2	-	= 1350 mg/kg (Rabbit)	-
-------------------------------	---	-------------------------	---

Information on physical, chemical and toxicological effects**Symptoms**

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Carcinogenicity**

This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Benzyl alcohol 100-51-6	35: 3 h <i>Anabaena variabilis</i> mg/L EC50	460: 96 h <i>Pimephales promelas</i> mg/L LC50 static 10: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static	EC50 = 50 mg/L 5 min EC50 = 63.7 mg/L 15 min EC50 = 63.7 mg/L 5 min EC50 = 71.4 mg/L 30 min	23: 48 h water flea mg/L EC50
Ethylene glycol monophenyl ether 122-99-6	500: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	337 - 352: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 366: 96 h <i>Pimephales promelas</i> mg/L LC50 static 220 - 460: 96 h <i>Leuciscus idus</i> mg/L LC50 static	EC50 = 32.4 mg/L 5 min EC50 = 880 mg/L 17 h	500: 48 h <i>Daphnia magna</i> mg/L EC50
Ethanolamine 141-43-5	15: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	227: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 3684: 96 h <i>Brachydanio rerio</i> mg/L LC50 static 300 - 1000: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 114 - 196: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 200: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through	EC50 = 110 mg/L 17 h EC50 = 12200 mg/L 2 h EC50 = 13.7 mg/L 30 min	65: 48 h <i>Daphnia magna</i> mg/L EC50
Octanoic Acid 124-07-2		310: 96 h <i>Oryzias latipes</i> mg/L LC50 semi-static 110: 96 h <i>Brachydanio rerio</i> mg/L LC50 semi-static		170: 24 h <i>Daphnia magna</i> mg/L EC50
Sodium metasilicate 6834-92-0		210: 96 h <i>Brachydanio rerio</i> mg/L LC50 semi-static 210: 96 h <i>Brachydanio rerio</i> mg/L LC50		216: 96 h <i>Daphnia magna</i> mg/L EC50
Sodium hydroxide 1310-73-2		45.4: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static		

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Benzyl alcohol 100-51-6	1.1
Ethylene glycol monophenyl ether 122-99-6	1.13
Ethanolamine 141-43-5	-1.91
Octanoic Acid 124-07-2	2.92

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical Name	California Hazardous Waste Status
Sodium hydroxide 1310-73-2	Toxic Corrosive

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1760
Proper Shipping Name Corrosive liquid, n.o.s. (Ethanolamine, Sodium hydroxide)
Hazard Class 8
Packing Group II

IATA

UN/ID No UN1760
Proper Shipping Name Corrosive liquid, n.o.s. (Ethanolamine, Sodium hydroxide)
Hazard Class 8
Packing Group II

IMDG

UN/ID No UN1760
Proper Shipping Name Corrosive liquid, n.o.s. (Ethanolamine, Sodium hydroxide)
Hazard Class 8
Packing Group II

15. REGULATORY INFORMATION

International Inventories

Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sodium hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene glycol monophenyl ether - 122-99-6	122-99-6	<10.0	1.0

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide 1310-73-2 (1.1)	1000 lb			X

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Benzyl alcohol 100-51-6		X	X
Ethylene glycol monophenyl ether 122-99-6	X		X
Ethanolamine 141-43-5	X	X	X
Sodium hydroxide 1310-73-2	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	3	0	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	Not determined	Not determined	Not determined	Not determined

Issue Date: 27-Dec-2011
Revision Date: 28-May-2013
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet