Material Safety Data Sheet This Material Safety Data Sheet is prepared in accordance with 29 CFR 1910.1200

Protective Clothing	Protective Clothing Hazardous Material Information System (U.S.A.)		National Fire Protection Association (U.S.A.)	
	Health Flammability Reactivity	2 2 0	Flammability Reactivity	
	Personal Protection	X	Specific Hazard	
Section I. Product Identification and Uses				

Section I. Product Identification and Uses			
Common/Trade name	SSS NewAge OMU 45 23043	TSCA	All components found in TSCA inventory
Synonyms	Urethane Finish For Wood Gym Floors	CAS#	NI/A
Chemical name	Not applicable.	CAS#	N/A
Chemical formula	Not Applicable		
Chemical family	Not Applicable		
Supplier	Triple S 2 Executive Park Drive Billerica, MA 01862		
Phone:	978-667-7900 Emergency Medical # 888-779-1339		

Section IA.	First Aid Measures
Eye contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	Wash with soap and water. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Section II. Hazardous Ingredients				
Name	CAS#	% by Weight	TLV/PEL	LC ₅₀ /LD ₅₀
Mineral Spirits	8052-41-3	0-100	TWA: 500 (ppm) TWA: 100 (ppm) from OSHA (PEL)	Not available.
Oil Modified Urethane Resin Alkyd Resin Aluminum Complex Methyl Ethyl Ketoxime	N/A N/A N/A 96-29-7	20-50 0-30 0-5 0-5	Not available. Not available. Not available.	Not available. Not available. Not available.

Physical State and Appearance	Liquid	Odor	Characteristic.	
рН	N/A	Taste	Not available.	
Odor threshold	Not available.	Color	Amber.	
Volatility	Not available.			

SSS NewAge OMU 45 23043		Page Number: 2
Boiling/Condensation point	148.89°C (300°F)	
Specific gravity	0.87 (Water = 1)	
Vapor Density	>1 (Air = 1)	
Vapor pressure	<10mm Hg @ 68°F	
Evaporation rate	<1	
Conditions of instability		
Dispersion properties		
Solubility	Miscible in water.	

Section IV. Fire and Explosion Data		
The product is:	COMBUSTIBLE.	
Fire degradation products	Not Applicable	
Flash points	CLOSED CUP: (105°F).	
Flammable limits	LOWER: 1% UPPER: 6%	
Fire extinguishing procedures	Use dry chemical or CO2.	
Flammability	COMBUSTIBLE.	
Risks of explosion	Drums Heated By Fire Can explode	

Section V. Reactivity Data		
Stability	Stable	
Hazardous Decomposition Products	Will not occur.	
Products of degradation		
Reactivity	Not available.	

Section VI. Toxicological Properties			
Routes of entry	Eye Contact Skin contact. Ingestion.		
TLV	Mineral Spirits TWA: 500 (ppm) TWA: 100 (ppm) from OSHA (PEL)		
	Consult local authorities for acceptable exposure limits.		
Toxicity to animals	not available		
Chronic effects on humans	Repeated skin exposure can produce local skin destruction, or dermatitis.		
Acute effects on humans	This product is an eye irritant. May cause mild irritation to the skin.		

Continued on Next Page

SSS	NewAge	OMU	<i>4</i> 5
2304	3		

Page Number: 3

Section VII. Preventive Measures

Storage Combustible materials should be stored away from extreme heat and away from strong oxidizing

agents. Keep out of reach of children. For Institutional and Commercial Use

Precautions Avoid contact with skin and eyes. Keep away from heat. Keep away from sources of ignition.

Small spill and leak Safety glasses recommended.

Large spill and leak Absorb with DRY earth, sand or other non-combustible material.

Protective clothing in Splash goggles. Gloves. Wear appropriate respirator when ventilation is inadequate.

case of large spill

Section VIII. Classification

DOT



Federal and State Regulations

Section IX. Protective Clothing



Section X. Other Information

Validated by CRushton on 4/9/2008.

Verified by CRushton.

Printed 4/9/2008.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.