



Safety Data Sheet

Issue Date: 27-Dec-2011

Revision Date: 22-Dec-2017

Version 2

1. IDENTIFICATION

Product Identifier

Product Name Buckeye Coliseum 450

Other means of identification

SDS # BE-5184
Product Code 5184
UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use Oil Modified Wood Floor Finish.

Details of the supplier of the safety data sheet

Supplier Address

Buckeye International, Inc.
2700 Wagner Place
Maryland Heights, MO 63043 USA

Emergency Telephone Number

Company Phone Number 1-314-291-1900

Emergency Telephone (24 hr)

Transportation - INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)
Medical - (International) 1-651-632-8956 (North America) 1-800-303-0441

2. HAZARDS IDENTIFICATION

Appearance Clear light amber solution

Physical State Liquid

Odor Mineral spirits

Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 1B
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Hazards Not Otherwise Classified (HNOC)

Causes mild skin irritation

Signal Word

Danger

Hazard Statements

Harmful if inhaled
May cause genetic defects
May damage fertility or the unborn child
May be fatal if swallowed and enters airways
Flammable liquid and vapor

**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash it before reuse
 If skin irritation occurs: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Get medical attention if symptoms persist
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting
 IN CASE OF FIRE: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Petroleum Distillates, Hydrotreated light	64742-47-8	>30
Proprietary Resin	Proprietary	>48
Naphtha (petroleum), heavy straight-run	64741-41-9	10-15
Xylene	1330-20-7	<5
N-methyl-2-pyrrolidone	872-50-4	<5
Ethylbenzene	100-41-4	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	If exposed or concerned: Get medical advice/attention.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. Get medical attention if irritation occurs.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if irritation persists. If not breathing give artificial respiration, preferably mouth-to-mouth.
Ingestion	IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Drink 2-3 large glasses of water. Immediately call a poison center or doctor/physician. Never give anything by mouth to an unconscious person.

Most important symptoms and effects

Symptoms	Causes mild skin irritation. Eye contact may cause redness or burning sensation. Inhalation causes irritation of throat and dizziness. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Ingestion may cause nausea and headache. May be harmful or fatal if swallowed and enters airways.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Foam. Dry chemical. Water spray (fog).

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Flammable liquid and vapor.

Hazardous Combustion Products Carbon oxides.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Water spray may be used to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protection recommended in Section 8.
Environmental Precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Pick up with dry mop, absorbent material, towels, or rags. Clean area with mineral spirits. Allow residue to evaporate. Allow floor to dry before allowing traffic.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling	Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Avoid contact with skin, eyes or clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Keep containers closed when not in use. Empty containers may contain flammable vapors/residue. Do not cut, weld, or puncture container. Dust from screening floors and finish soaked rags can auto ignite. Immerse dust in water and open rags to air dry before discarding the waste.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up.
Incompatible Materials	Strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Proprietary Resin	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Dipropylene Glycol Monomethyl Ether (DPM) 34590-94-8	STEL: 150 ppm TWA: 100 ppm S*	TWA: 100 ppm TWA: 600 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m ³ (vacated) S* S*	IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m ³ STEL: 150 ppm STEL: 900 mg/m ³

Appropriate engineering controls

Engineering Controls	Ensure adequate ventilation, especially in confined areas. Eyewash stations. Showers.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Splash goggles or safety glasses.
Skin and Body Protection	Rubber gloves. Suitable protective clothing.
Respiratory Protection	None under normal use. If air monitoring levels demonstrate levels above applicable limits, a properly fitted respirator should be worn during application.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State	Liquid	Odor	Mineral spirits
Appearance	Clear light amber solution	Odor Threshold	Not determined
Color	Clear light amber		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	139 °C / 282 °F	
Flash Point	38 °C / 100 °F	
Evaporation Rate	0.6	(butyl acetate = 1)
Flammability (Solid, Gas)	Liquid-Not applicable	
Upper Flammability Limits	6.0%	
Lower Flammability Limit	1.0%	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Specific Gravity	0.89	
Water Solubility	Insoluble in water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization	Hazardous polymerization does not occur.
---------------------------------	--

Conditions to Avoid

Keep separated from incompatible substances. Keep out of reach of children.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	Causes mild skin irritation.
Inhalation	Harmful if inhaled.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Distillates, Hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 47635 mg/L (Rat) 4 h
N-methyl-2-pyrrolidone 872-50-4	= 3598 mg/kg (Rat)	= 8 g/kg (Rabbit)	= 3.1 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Dipropylene Glycol Monomethyl Ether (DPM) 34590-94-8	= 5230 mg/kg (Rat)	= 9500 mg/kg (Rabbit)	-
2-(Dimethylamino) ethanol 108-01-0	= 1803 mg/kg (Rat)	= 1370 µL/kg (Rabbit)	= 6.1 mg/L (Rat) 4 h = 1641 ppm (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		
Ethylbenzene 100-41-4	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity May damage fertility or the unborn child.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum Distillates, Hydrotreated light 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static		
Naphtha (petroleum), heavy straight-run 64741-41-9	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50			
Xylene 1330-20-7		13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
N-methyl-2-pyrrolidone 872-50-4	500: 72 h Desmodesmus subspicatus mg/L EC50	832: 96 h Lepomis macrochirus mg/L LC50 static 1072: 96 h Pimephales promelas mg/L LC50 static 1400: 96 h Poecilia reticulata mg/L LC50 static		4897: 48 h Daphnia magna mg/L EC50
Ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Dipropylene Glycol Monomethyl Ether (DPM) 34590-94-8		10000: 96 h Pimephales promelas mg/L LC50 static		1919: 48 h Daphnia magna mg/L LC50
2-(Dimethylamino) ethanol 108-01-0	35: 72 h Desmodesmus subspicatus mg/L EC50	81: 96 h Pimephales promelas mg/L LC50 static		98.77: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Xylene 1330-20-7	3.15
N-methyl-2-pyrrolidone 872-50-4	-0.46
Ethylbenzene 100-41-4	3.118

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1263
Proper Shipping Name Paint related material
Hazard Class 3
Packing Group III

IATA

UN/ID No UN1263
Proper Shipping Name Paint related material
Hazard Class 3
Packing Group III

IMDG

UN/ID No	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	III

15. REGULATORY INFORMATION**International Inventories**

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Petroleum Distillates, Hydrotreated light	Present	X		Present		Present	X	Present	X	X
Proprietary Resin	Present	X		Present		Present	X	Present	X	X
Naphtha (petroleum), heavy straight-run	Present	X		Present			X	Present	X	X
Xylene	Present	X		Present		Present	X	Present	X	X
N-methyl-2-pyrrolidone	Present	X		Present		Present	X	Present	X	X
Ethylbenzene	Present	X		Present		Present	X	Present	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	<5	1.0
N-methyl-2-pyrrolidone - 872-50-4	872-50-4	<5	1.0
Ethylbenzene - 100-41-4	100-41-4	<1	0.1
Dipropylene Glycol Monomethyl Ether (DPM) - 34590-94-8	34590-94-8	0.58	1.0

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb			X
Ethylbenzene	1000 lb	X	X	X

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
N-methyl-2-pyrrolidone - 872-50-4	Developmental
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Proprietary Resin	X	X	X
Xylene 1330-20-7	X	X	X
N-methyl-2-pyrrolidone 872-50-4	X	X	X
Ethylbenzene 100-41-4	X	X	X
Dipropylene Glycol Monomethyl Ether (DPM) 34590-94-8	X	X	X
2-(Dimethylamino) ethanol 108-01-0	X	X	X

16. OTHER INFORMATION**NFPA****Health Hazards****Flammability****Instability****Special Hazards**

2

2

1

Not determined

HMIS**Health Hazards****Flammability****Physical Hazards****Personal Protection**

Not determined

Not determined

Not determined

Not determined

Issue Date:

27-Dec-2011

Revision Date:

22-Dec-2017

Revision Note:

Telephone number update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet